

Finex™

Air Spray Guns



HVLP Pressure Feed

Mini Gravity Feed

HVLP Gravity Feed

Lightweight, Ergonomic Air Spray Guns:

- Aircaps optimized for high quality spray performance
- Lightest trigger pull in its category
- Integrated air inlet adjustment (cheater) valve

Finex Pressure Feed Guns:

- Available in HVLP and Conventional technologies
- Needle/nozzle sizes offered in 0.04" (1.0 mm), 0.05" (1.2 mm), 0.055" (1.4 mm) and 0.07" (1.8 mm)

Finex Gravity Feed Guns:

- Mini and Standard Gravity Feed offered in a wide variety of needle/nozzle sizes
- Plastic cup included with the gun
- 3M™ PPS™ and aluminum cups available

Ordering Information for Finex Guns and Accessories

Gun Style	Gun Part Number	Needle/Nozzle Size		Needle, Nozzle Air Cap Kit	Needle Packing Kit	Gravity Cup Kits	PPS Adapter
		in	mm				
Pressure Feed Standard HVLP	289247	0.039	1.0	289301	288891		
	289248	0.047	1.2	289302			
	289249	0.055	1.4	289303			
	289250	0.071	1.8	289304			
Pressure Feed Conventional	289252	0.039	1.0	289306	288891		
	289253	0.047	1.2	289307			
	289254	0.055	1.4	289308			
	289255	0.071	1.8	289309			
Gravity Feed Mini-HVLP	289256	0.024	0.6	289286	288890	289323 (125 cc Plastic)	289520
	289257	0.031	0.8	289287			
	289258	0.039	1.0	289288			
	289259	0.047	1.2	289289			
	289260	0.055	1.4	289290			
Gravity Feed Standard Conventional	289243	0.051	1.3	289292	288891	289322 (600 cc Plastic)	289520
	289244	0.055	1.4	289293			
	289245	0.059	1.5	289294			
	289246	0.071	1.8	289295			
Gravity Feed Standard HVLP	289237	0.039	1.0	289296	288891	289322 (600 cc Plastic)	289520
	289238	0.051	1.3	289297			
	289239	0.055	1.4	289298			
	289240	0.059	1.5	289299			
	289241	0.071	1.8	289300			

Technical Data

Maximum air inlet pressure 100 psi (7 bar, 0.7 MPa)
 Maximum fluid working pressure 100 psi (7 bar, 0.7 MPa)
 Gravity Feed:
 Maximum HVLP inbound air pressure. 29 psi (2 bar, 0.2 MPa)*
 Pressure Feed:
 Maximum HVLP inbound air pressure. 24 psi (1.7 bar, 0.17 MPa)*
 Air consumption
 Mini HVLP Gravity 7.0 SCFM at 29 psi (2.0 bar, 0.2 MPa)
 Conventional Gravity 9.5 SCFM at 43 psi (3.0 bar, 0.3 MPa)
 HVLP Gravity 9.5 SCFM at 29 psi (2.0 bar, 0.2 MPa)
 HVLP Pressure 11.8 SCFM at 24 psi (1.7 bar, 0.17 MPa)
 Conventional Pressure 11.0 SCFM at 50 psi (3.4 bar, 0.34 MPa)
 Fluid and air operating temperature range 32-109°F (0-43° C)
 Spray Gun
 Air inlet. 1/4 npsm (R1/4-19)
 Fluid inlet (pressure feed) 3/8-18 npsm (R3/8-19)
 Mini HVLP Gravity weight with cup 0.9 lb (0.4 kg)
 Gravity Feed weight with cup 1.1 lb (0.5 kg)
 Pressure Feed weight 0.8 lb (0.37 kg)
 Wetted parts. Aluminum, stainless steel, engineered plastic

*Produces 10 psi (0.07 MPa, 0.7 bar) spraying pressure at aircap.

Accessories

3M's PPS Accessories
 For use with gravity feed guns

6 oz (150 ml) 3M PPS
 234941 Cup and Collar (box of 8)
 234940 Lid and Liner (box of 50)
 234942 Measurement Insert (box of 50)

25 oz (650 ml) 3M PPS
 234771 Cup and Collar (box of 8)
 234772 Lid and Liner (box of 50)
 15F531 Measurement Insert (box of 100)

32 oz (850 ml) 3M PPS
 234937 Cup and Collar (box of 4)
 234938 Lid and Liner (box of 25)
 234939 Measurement Insert (box of 100)

Aluminum Cups
 289858 125 cc Aluminum
 289859 250 cc Aluminum
 289860 600 cc Aluminum



For more information visit www.graco.com/finishing or call **1-877-844-7226**

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.
877.84GRACO (1-877-844-7226) or visit us at www.graco.com.

©2010 Graco Inc. Form No. 339461 Rev. B 7/10 Printed in the U.S.A.
 All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

